www.aquafilter.com

RP65155616

The Clear Choice Water Filtration Systems





General Description:

AQUAFILTER offers RP65253616 - 6 stage Reverse Osmosis system with AIMRO mineralizing cartridge and a pump. Made of NSF and WRAS certified components.

Due to the high membrane quality it is possible to purify up to 280 liters of water per day. Small micron rating 0,0001 μ m, allows to remove most contaminants from water including bacteria and viruses.

System is equipped with post filtration in-line cartridge (AICRO), which improves the taste and aroma of water and AIMRO mineralizing cartridge which enriches water with minerals such as calcium and magnesium. The system is offered with a double faucet which allows water collection directly after RO membrane and/or after re-mineralization.

Additionally a booster pump was added, this allows to install the system in installation where water pressure is lower than 2,8 bar.

Set includes: RP65155616 system, FCPS5, FCCA, FCCBL, AICRO, AIMRO cartridges and TFC-75F RO membrane, M1207515 pump, FXFCH16-C faucet, feed water connector 1/2", tubing, tank, instruction, accessories and color box.

Features:

- High quality
- Competitive Pricing
- Six Stages of Filtration
- Hand Built & Factory Tested
- Easy Maintenance
- Easy to install with System Specifications - Systems equipped with modern faucet,
- all installation accessories, ready to install
- Improved taste and odor of waterDesigned for enhanced dirt-holding
- capacity
- Great-tasting water for drinking and cooking
- Produces clearer ice
- Diaphragm pump included
- Less expensive than bottled water - Made in EU
- Manufactured from FDA CFR-21 compliant materials

Recomendations for Use:

- Point-of-Use (POU) systems can filter out bad tastes, colors or odors, which pose no health risk but still affect the water quality
- This system will improve the flavor of
- water used for drinking and cooking Perfect for almost any household and
- will easily fit into any space - Kitchen compact, undercounter, home
- and apartment size - Recommended for Families

www.aquafilter.com



The Clear Choice Water Filtration Systems

RP65253616

6 Stage Reverse Osmosis System with Pump and Mineralizing Cartridge



Specifications:

System dimensions (H x W x L): 400 x 140 x 340 (mm) Tank dimensions (H x D): 380 x 280 (mm) Connection adapter: 1/2" Working Temp: 2°C - 45°C (35° F - 113° F) Operating Pressure: Max. 6.0 bar (90 psi) Min. 2.8 bar (40 psi) Typical Rejection Rate: 98% TDS (Total Dissolved Solids) pH Parameters: Maximum 11 Minimum 2 Iron: Maximum 0.2 ppm TDS (Total Dissolved Solids) < 1800 ppm Turbidity < 5 NTU Tank Capacity: 12 liters

The package contains:

The RP65253616 comes complete with the following cartridges: FCPS5, FCCA, FCCBL, AICRO, AIMRO
 RO membrane element type: TFC-75F Manufactured by Aquafilter
 Diaphragm pump (75 GPD)
 3.2 Gallons Plastic - Water Storage Tank (capacity 12 liters)
 NSF certified, Filter Housing (double o'ring)
 Automatic Shut-off Valve, Mini Flow Restrictor, Check Valve
 Long Reach Chrome Faucet: FXFCH16-C
 Feed water connector: 1/2*
 Drain Saddle Valve
 Four Color Coded 1/4 Inch Tubing for System Connection
 System built with quick type fittings
 Completely Assembled
 Manual instructions
 Color box
 100% Factory Tested and Sterilized Ready for Installation

	# STAGE	COMPONENT	FUNCTION
FCPS5	1	Sediment Pre-Filter Spun-bounded polypropylene	5 micron sediment filter traps dirt, sediment, rust and other particulate matter.
FCCA	2	Carbon Cartridge Activated coconut shell carbon (GAC)	Coconut shell carbon reduce chlorine, color, odor and other organic impurities
FCCBL	3	Carbon Cartridge Pre-Filter Extruded activated carbon	Carbon block filter is used to reduce chlorine, color, odor and other organic impurities
TFC-75F	4	Reverse Osmosis Membrane Thin Film Composite (75 GPD), 0.0001 micron	Semi-permeable membrane will remove salts, minerals, metals, bacteria, viruses, cysts, TDS, Hardness, Fluorides, Pesticides, Lead, Mercury, Cadmium & Arsenic and more. Due to the time needed to remove all these ingredients your RO system includes a storage tank.
AICRO	5	Post-Carbon Filter GAC activated carbon	Post Carbon Filtration granular activated coconut shell carbon cartidge provides the final polishing and assures good tasting drinking water
AIMRO	6	Post-mineralizing cartridge Re-Mineralization Filter Cartridge	Enriches water with elements that are necessary for human body, such as: calcium, magnesium.
\bigcirc	<u></u>		<u> </u>
FXFCH16-C		PPS5 FCCA	FCBL AICRO AIMRO TFC-75F
EXFCH16-C Double Filter faucet with ceramic value	10" filter housing 10" melt-blow	PS5 polypropylene idge - 5 µm	
Double Filter faucet	10° filter housing H10A series 10° melt-blow filter cart	v polypropylene 10" GAC	10" carbon in-line coconunt mineralizing cartridge Reverse Osmosis

• West imitation systems can replicate the presence of contaminants, and using some water matching systems can reply reduct use presence of matching anisms of our el contaminants with potential mean replacement of the filter cartification systems can reply reduct to perform properly.
• Replace the filter cartification is a single system of the filter

purchase. This limited warranty does not apply to failures that result from abuse, misuse, alteration or failure to properly comply with installation, or cartridge change instructions. We strongly recommend adding to all point of use filtration systems a Pressure Limiting Valve (PLV-0104 series) to guard against unwanted extreme water pressure events pressure increases, surges, and water hammer which could occur in the water pipes. Not having one installed could mean that if you ever did have to claim damage caused by a burst water filter system, the claim will be denied.

All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter. Inc. and may not be used without our express written permission

Aquafilter Manufacturing Facility





FD/A



Aquafilter Europe 91-222 Lodz, Poland

us@aquafilter.com

de@aquafilter.com

pl@aquafilter.com











